1/2

PRODUCT FICHE

	Built-In Oven 736752 OP543PGUK	
	USP :	
	SilverMatte	v
	MultiFlow 360°	v
	Auto programme	×
	Door type	Quadruple glazed oven door with double heat deflector (UltraCoolDoorQuadro+)
	STEPBake	A.
	Door hinge	GentleClose door hinge
	SlowBake	×
	Yoghurt	×
	Dehydration	✓
	Oven type	Multisystem oven BigSpace - 71 I SuperSize baking area
	TouchFree Inox	✓
	Maximum oven temperature	300 °C
	Heating types	Pyrolytic cleaning
	Cooling fan	Dynamic oven cooling plus - DC+
	Sabbath mode	×
	HomeMade Plus shape	A.
	Pyrolytic self cleaning oven	Pyrolytic cleaning
	Energy class	A+



Basic information :

BrandHISENSECommercial codeOP543PGUKInternal article number736752EAN code3838782436802Main colour of productJet blackConstruction typeBuilt-InType of controlElectronicMicrowave functionYesDoor MaterialGlassEnergy inputGlassConstruction rating0 WElectricin rating300 WElectricin rating0 WElectricial supply cord 3 x100 WCorrent0,0 AVarge50% HzMarks of conformityCE_VDEGSLength of he product595 mmWithout plug, supply cord 3 x1.5Height of he product595 mmDepth of installation niche680 mmMithout plug he product680 mmMithout plug he product595 mmMithout plug he product595 mmDepth of installation niche0 mmDepth of installation niche595 mmMithout fulg hastallation niche595 mmMark hof installation niche0 mmMark width of installation niche0 mmMark width of installation niche0 mmMark width of installation niche0 mmDepth of stallation niche0 mmDepth	Product group	Built-In Oven
Commercial codeOP543PGUKInternal article number736752EAN code383782436802Main colour of productJet blackConstruction typeBuilt-inType of controlElectronicMicroware functionYesAre any hobs controls integrated?YesDoor MaterialElectricityConstruction ratingGlassEnergy inputElectricityCosting methodMultisystemGas connection rating0 WElectricit connection rating0,0 AVotage200-240 VFrequency0606 HzMarks of conformityCE,VDEGSLength of the product595 mmHeight of the product595 mmWith of the product691 mmHeight of the product691 mmWith of the product635 mmHeight of the packed product630 mmMin height of installation niche00 mmMax with of installation niche0 mmMax with of installation niche0 mm		
EAN code3838782436802Main colour of productJet blackConstruction typeBuilt-inType of controlElectronicMicrowave functionYesAre any hobs controls integrated?YesDoor MaterialGlassEnergy inputElectricityCosting methodMultisystemGas connection rating0 WElectricit connection rating00 WElectricit connection rating0.0 AVotage20-240 VFrequercy50/60 HzMarks of conformityCE, VDEGSLength of electricial supply cord 3 x 1.5Height of the product595 mmWithout plug, supply cord 3 x 1.5Height of the product595 mmWithout plug, supply cord 3 x 1.5Height of the product595 mmWithout plug, supply cord 3 x 1.5Height of the product595 mmWithout plug, supply cord 3 x 1.5Height of the product595 mmWithout plug, supply cord 3 x 1.5Height of the product595 mmWithout plug, supply cord 3 x 1.5Height of the product595 mmMicht of the product595 mmWithout plug to finatalation niche590 mmMin height of instalation niche590 mmMax widt of instalation niche0 mmMin widt of instalation niche0 mm		OP543PGUK
Main colour of productJet blackConstruction typeBuilt-inType of controlElectronicMicrowave functionYesAre any hobs controls integrated?YesDor MaterialGlassEnergy inputElectricityCooking methodMultisystemGas connection rating0 WElectrical connection rating3400 WCurrent0,0 AVoltage200-240 VFrequency50/60 HzMarks of conformityCE-VDEGSLength of electrical supply cord0 cmVilto typeWithout plug, supply cord 3 x 1.5Height of the product595 mmDepth of the product635 mmDepth of the packed product630 mmMin height of installation niche590 mmMark bight of installation niche0 mmMark bight of installation niche0 mm	Internal article number	736752
Construction typeBuilt-inType of controlElectronicMicrowave functionYesAre any hobs controls integrated?YesDor MaterialGlassEnergy inputElectricityCooking methodMultisystemGas connection rating0 WElectrical connection rating0.0 ACurrent0,0 AVoltage20-240 VFrequencyS0/60 HzMarks of conformityCE,VDEGSLength of the product595 mmVight of the product595 mmVight of the product595 mmVight of the product607 mmVight of the product630 mmWight of the product630 mmWight of the product630 mmMarks of installation niche590 mmMin wight of installation niche590 mmMax wight of installation niche0 mm	EAN code	3838782436802
Construction typeBuilt-inType of controlElectronicMicrowave functionYesAre any hobs controls integrated?YesDor MaterialGlassEnergy inputElectricityCooking methodMultisystemGas connection rating0 WElectrical connection rating0.0 ACurrent0,0 AVoltage20-240 VFrequencyS0/60 HzMarks of conformityCE,VDEGSLength of the product595 mmVight of the product595 mmVight of the product595 mmVight of the product607 mmVight of the product630 mmWight of the product630 mmWight of the product630 mmMarks of installation niche590 mmMin wight of installation niche590 mmMax wight of installation niche0 mm	Main colour of product	Jet black
Microwave functionYesAre any hobs controls integrated?YesDor MaterialGlassEnergy inputElectricityCooking methodMultisystemGas connection rating0 WElectrical connection rating0,0 ACurrent0,0 AVoltage220-240 VFrequency50/60 HzMarks of conformityCE,VDEGSLength of electrical supply cord 3 x 1.5Height of the product595 mmVidth of the product595 mmWidth of the product691 mmWidth of the product635 mmDepth of the product635 mmDepth of installation niche690 mmMax width of installation niche0 mmMax width of installation niche0 mm		Built-in
Are any hobs controls integrated?YesDoor MaterialGlassEnergy inputElectricityCooking methodMultisystemGas connection rating0 WElectrical connection rating3400 WCurrent0,0 AVoltage220-240 VFrequency50/60 HzMarks of conformityCE,VDEGSLength of electrical supply cord0 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmUth of the product595 mmWidth of the product691 mmWidth of the product691 mmWidth of in stallation niche680 mmMax width of installation niche0 mmMax width of installation niche0 mm	Type of control	Electronic
Door MaterialGlassEnergy inputElectricityCooking methodMultisystemGas connection rating0 WElectrical connection rating3400 WCurrent0,0 AVoltage220-240 VFrequency50/80 HzMarks of conformityCE,VDEGSLength of electrical supply cord0 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmDopth of the product595 mmUvith of the product646 mmWith of the packed product635 mmWith of the packed product630 mmWith of installation niche590 mmMax height of installation niche504 mmMax width of installation niche564 mmMax width of installation niche564 mmMax width of installation niche564 mmMax width of installation niche0 mm	Microwave function	Yes
Energy inputElectricityCooking methodMultisystemGas connection rating0 WElectrical connection rating3400 WCurrent0,0 AVoltage220-240 VFrequency50/60 HzMarks of conformityCE_VDEGSLength of electrical supply cord 3 x 1.5Height of the product595 mmVoltade595 mmVoltade595 mmVoltade691 mmWith of the product691 mmWith of the packed product635 mmDepth of the packed product635 mmMin with of installation niche590 mmMark width of installation niche0 mmMark width of installation niche564 mmMax width of installation niche0 mm	Are any hobs controls integrated?	Yes
Cooking methodMultisystemGas connection rating0 WElectrical connection rating3400 WCurrent0,0 AVoltage220-240 VFrequency50/60 HzMarks of conformityCE,VDEGSLength of electrical supply cord0 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmDepth of the product595 mmWidth of the packed product691 mmWidth of the packed product691 mmWidth of installation niche590 mmMax keight of installation niche0 mmMax width of installation niche0 mmMax width of installation niche0 mm	Door Material	Glass
Gas connection rating0 WElectrical connection rating3400 WCurrent0,0 AVoltage220-240 VFrequency50/60 HzMarks of conformityCE,VDEGSLength of electrical supply cord0 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmUdth of the product595 mmWidth of the product595 mmUdth of the packed product691 mmWidth of installation niche680 mmMan keight of installation niche0 mmMax width of installation niche0 mmMax width of installation niche0 mm	Energy input	Electricity
Electrical connection rating3400 WCurrent0,0 AVoltage220-240 VFrequency5060 HzMarks of conformityCE,VDEGSLength of electrical supply cord0 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmVidth of the product595 mmDepth of the packed product691 mmWidth of the packed product635 mmWidth of installation niche590 mmMark eight of installation niche590 mmMark width of installation niche0 mmMax width of installation niche0 mmMax width of installation niche0 mm	Cooking method	Multisystem
Current0,0 ÅVoltage220-240 VFrequency50/60 HzMarks of conformityCE,VDEGSLength of electrical supply cord0 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmVidth of the product595 mmDepth of the product595 mmWidth of the product691 mmWidth of the packed product635 mmDepth of the packed product680 mmMin height of installation niche0 mmMax width of installation niche0 mm	Gas connection rating	
Voltage20-240 VFrequency50/60 HzMarks of conformityCE, VDEGSLength of electrical supply cord0 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWidth of the product595 mmDepth of the product595 mmHeight of the product691 mmWidth of the packed product635 mmWidth of the packed product635 mmDepth of the packed product635 mmMin height of installation niche590 mmMax width of installation niche0 mmMax width of installation niche0 mm	Electrical connection rating	3400 W
Frequency50/60 HzMarks of conformityCE,VDEGSLength of electrical supply cord0 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWidth of the product595 mmDepth of the product595 mmHeight of the packed product691 mmWidth of the packed product635 mmDepth of the packed product635 mmMin height of installation niche590 mmMax height of installation niche0 mmMax width of installation niche564 mmMax width of installation niche564 mmMax width of installation niche0 mm	Current	0,0 A
Marks of conformityCE,VDEGSLength of electrical supply cord0 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWidth of the product595 mmDepth of the product546 mmHeight of the packed product691 mmWidth of the packed product635 mmDepth of the packed product630 mmMin height of installation niche590 mmMax height of installation niche0 mmMax width of installation niche0 mmMax width of installation niche0 mm	Voltage	220-240 V
Length of electrical supply cord0 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWidth of the product595 mmDepth of the product546 mmHeight of the packed product691 mmWidth of the packed product635 mmDepth of the packed product630 mmMin height of installation niche590 mmMax height of installation niche0 mmMax width of installation niche564 mmMax width of installation niche0 mm	Frequency	50/60 Hz
Plug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWidth of the product595 mmDepth of the product546 mmHeight of the packed product691 mmWidth of the packed product635 mmDepth of the packed product630 mmMin height of installation niche590 mmMax height of installation niche0 mmMax width of installation niche564 mmMax width of installation niche0 mm	Marks of conformity	CE,VDEGS
Height of the product595 mmWidth of the product595 mmDepth of the product546 mmHeight of the packed product691 mmWidth of the packed product635 mmDepth of the packed product680 mmDepth of the packed product590 mmMin height of installation niche590 mmMax height of installation niche0 mmMin width of installation niche564 mmMax width of installation niche0 mm	Length of electrical supply cord	0 cm
Width of the product595 mmDepth of the product546 mmHeight of the packed product691 mmWidth of the packed product635 mmDepth of the packed product630 mmDepth of the packed product680 mmMin height of installation niche590 mmMax height of installation niche0 mmMin width of installation niche564 mmMax width of installation niche0 mm	Plug type	Without plug, supply cord 3 x 1.5
Depth of the product546 mmHeight of the packed product691 mmWidth of the packed product635 mmDepth of the packed product630 mmDepth of the packed product680 mmMin height of installation niche590 mmMax height of installation niche0 mmMin width of installation niche564 mmMax width of installation niche0 mm	Height of the product	
Height of the packed product691 mmWidth of the packed product635 mmDepth of the packed product680 mmMin height of installation niche590 mmMax height of installation niche0 mmMin width of installation niche564 mmMax width of installation niche0 mm	Width of the product	595 mm
Width of the packed product635 mmDepth of the packed product680 mmMin height of installation niche590 mmMax height of installation niche0 mmMin width of installation niche564 mmMax width of installation niche0 mm	Depth of the product	546 mm
Depth of the packed product680 mmMin height of installation niche590 mmMax height of installation niche0 mmMin width of installation niche564 mmMax width of installation niche0 mm	Height of the packed product	691 mm
Min height of installation niche590 mmMax height of installation niche0 mmMin width of installation niche564 mmMax width of installation niche0 mm	Width of the packed product	635 mm
Max height of installation niche0 mmMin width of installation niche564 mmMax width of installation niche0 mm	Depth of the packed product	680 mm
Min width of installation niche 564 mm Max width of installation niche 0 mm	Min height of installation niche	590 mm
Max width of installation niche 0 mm	•	
Depth of installation niche 550 mm	Max width of installation niche	
	Depth of installation niche	550 mm

Niek oor telek
Net weight
Gross weight
Automatic programmes
Type of control setting and signalling devices
Color / Material front
Grill power

Features :

Temperature control	N/A
Short description of the product	BO6PY4D1-42 - OP543PGUK
Timer	Yes
Integrated Cleaning system	Easy to clean enamel
Grids	1
Time control	Mehanical
Time-setting Options	Start and stop
Trays	2
Control panel information	Dot matrix display
Oven interior	N/A
Motorized Turn Spit	No
Additional equipment included	Deep baking pan - 1 Baking tray EM - 1 Oven grid - 1
Safety device	Thermo electric oven protection Oven door switch
Oven lighting	Yes
Position of interior lights	2
Meat probe	Yes
Oven guides	Wire type 1x

42,2 Kg 46,5 Kg N/A Color DOT MATRIX Jet black 0 W

Energy label information / Performance :

Standard load cooking time - fan cooking	42.5 min
Standard load cooking time - conventional cooking	46.2 min
The power consumption in off-mode	1,0 W
Energy consumption per cycle conventional (2010/30/ES)	1,0 kWh/Zyklus
Energy consumption gas oven per cycle conventional (2010/30/ES)	0,0 Mj
Energy consumption per cycle forced air convection (2010/30/ES)	0,69 kWh/cycle
Usable volume of cavity (2010/30/ES)	711
Number of cavities - NEW (2010/30/EC)	1
Energy consumption gas oven per cycle conventional - NEW (2010/30/EC)	0,00
Energy efficiency index (2010/30/EC)	81,2
Energy efficiency class	A+
Energy consumption conventional	1,0 kWh
Noise	47 db(A)re 1 pW
Energy consumption forced air convection	0,69 kWh
Useable volume (of cavity)	71
Product size	Large